

Cosses tubulaires DIN 46235

| Référence n° | Section mm ² | Alésage Ø | Indice | Dimensions mm | | | | | | | | 100 pcs ~ kg | pcs |
|--------------|-------------------------|-----------|--------|---------------|------|------|------|------|------|------|------|--------------|-------|
| | | | | d1 | a | b | d2 | d4 | c1 | c2 | l | | |
| 110R10 | 150 | M 10 | 22 | 17,0 | 35 | 34,0 | 10,5 | 23,5 | 15,0 | 16,0 | 78 | 16,38 | 10 |
| 110R12 | | M 12 | 22 | 17,0 | 35 | 34,0 | 13,0 | 23,5 | 16,0 | 17,0 | 78 | 16,29 | 25 |
| 110R14 | | M 14 | 22 | 17,0 | 35 | 34,0 | 15,0 | 23,5 | 19,0 | 20,0 | 78 | 16,38 | 10 |
| 110R16 | | M 16 | 22 | 17,0 | 35 | 34,0 | 17,0 | 23,5 | 19,0 | 20,0 | 78 | 16,17 | 10 |
| 110R20 | | M 20 | 22 | 17,0 | 35 | 40,0 | 21,0 | 23,5 | 21,0 | 22,0 | 78 | 15,90 | 10 |
| 111R10 | | 185 | M 10 | 25 | 19,0 | 40 | 37,0 | 10,5 | 25,5 | 15,0 | 16,0 | 82 | 18,96 |
| 111R12 | M 12 | | 25 | 19,0 | 40 | 37,0 | 13,0 | 25,5 | 16,0 | 17,0 | 82 | 18,11 | 10 |
| 111R14 | M 14 | | 25 | 19,0 | 40 | 37,0 | 15,0 | 25,5 | 19,0 | 20,0 | 82 | 19,21 | 10 |
| 111R16 | M 16 | | 25 | 19,0 | 40 | 37,0 | 17,0 | 25,5 | 19,0 | 20,0 | 82 | 18,74 | 25 |
| 111R20 | M 20 | | 25 | 19,0 | 40 | 40,0 | 21,0 | 25,5 | 21,0 | 22,0 | 82 | 18,69 | 10 |
| 112R12 | 240 | | M 12 | 28 | 21,5 | 40 | 42,0 | 13,0 | 29,0 | 16,0 | 17,0 | 92 | 27,00 |
| 112R14 | | M 14 | 28 | 21,5 | 40 | 42,0 | 15,0 | 29,0 | 19,0 | 20,0 | 92 | 27,58 | 10 |
| 112R16 | | M 16 | 28 | 21,5 | 40 | 42,0 | 17,0 | 29,0 | 19,0 | 20,0 | 92 | 27,37 | 25 |
| 112R20 | | M 20 | 28 | 21,5 | 40 | 45,0 | 21,0 | 29,0 | 21,0 | 22,0 | 92 | 26,88 | 10 |
| 113R14 | 300 | M 14 | 32 | 24,5 | 50 | 46,0 | 15,0 | 32,0 | 19,0 | 22,0 | 100 | 33,29 | 5 |
| 113R16 | | M 16 | 32 | 24,5 | 50 | 46,0 | 17,0 | 32,0 | 19,0 | 22,0 | 100 | 32,94 | 5 |
| 113R20 | | M 20 | 32 | 24,5 | 50 | 46,0 | 21,0 | 32,0 | 22,0 | 22,0 | 100 | 33,24 | 5 |
| 114R14 | 400 | M 14 | 38 | 27,5 | 70 | 54,0 | 15,0 | 38,5 | 25,0 | 25,0 | 115 | 69,38 | 5 |
| 114R16 | | M 16 | 38 | 27,5 | 70 | 54,0 | 17,0 | 38,5 | 25,0 | 25,0 | 115 | 68,54 | 5 |
| 114R20 | | M 20 | 38 | 27,5 | 70 | 54,0 | 21,0 | 38,5 | 25,0 | 25,0 | 115 | 65,40 | 5 |
| 115R16 | 500 | M 16 | 42 | 31,0 | 70 | 60,0 | 17,0 | 42,0 | 25,0 | 25,0 | 125 | 83,31 | 1 |
| 115R20 | | M 20 | 42 | 31,0 | 70 | 60,0 | 21,0 | 42,0 | 25,0 | 25,0 | 125 | 81,58 | 1 |
| 116R16 | 625 | M 16 | 44 | 34,5 | 80 | 64,0 | 17,0 | 44,0 | 25,0 | 25,0 | 135 | 79,60 | 1 |
| 116R20 | | M 20 | 44 | 34,5 | 80 | 64,0 | 21,0 | 44,0 | 25,0 | 25,0 | 135 | 79,69 | 1 |
| 117R16 | 800 | M 16 | 52 | 40,0 | 100 | 75,0 | 17,0 | 52,0 | 30,0 | 30,0 | 165 | 150,00 | 1 |
| 117R20 | | M 20 | 52 | 40,0 | 100 | 75,0 | 21,0 | 52,0 | 30,0 | 30,0 | 165 | 149,00 | 1 |
| 118R16 | 1000 | M 16 | 58 | 44,0 | 100 | 83,0 | 17,0 | 58,0 | 30,0 | 30,0 | 165 | 199,00 | 1 |
| 118R20 | | M 20 | 58 | 44,0 | 100 | 83,0 | 21,0 | 58,0 | 30,0 | 30,0 | 165 | 195,00 | 1 |

↻ Douilles de réduction pour conducteurs compactés : voir page 28.

↻ Outillage : voir page 29.

